

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Data transmission cables and systems**with type designation(s)
AICI F6 (NEK 606)

Issued to

Sohome AS
Bergen, Norway

is found to comply with

Det Norske Veritas' Rules for Classification of Ships, High Speed & Light Craft and Det Norske Veritas' Offshore Standards**Type Approval Programme No. 6-827.50-1****IEC 60332-3-24 (2009-02)****IEC 60332-3-22 (2009-02)****IEC 60754-1/2 (2011-11)****IEC 60794-1-1 (2011-09)****IEC 61034-1/2 Ed. 3.1 (2013-06)****NEK TS 606 (2009-05)****Application :****Fiber optic cable. Halogen free. Low smoke.****Voltage (kV)****Temp. class (°C)**This Certificate is valid until **2019-07-07**.Issued at **Høvik** on **2015-07-08**DNV GL local station: **Bergen**Approval Engineer: **Ludovico Gullifa**for **DNV GL**

Marit Laumann
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

Product description

Type AICI F6 (NEK 606)

Optical fibres

Fibre type	9/125	50/125-OM2	50/125-OM3	62.5/125-OM1
Fiber data sheet	C03	C34	C31	C02
IEC60793-2-10, 20, 50 cat.	B.1.3	A1a.1	A1a.2	A1b
IEC11801 classification	OS2	OM2	OM3	OM1
ANSI/TIA/EIA classification	CAAB	AAAB	AAAC	AAAA
ITU-T type	G652.D	G651.1	G651.1	-
Core diameter	See mode field diameter	50 ± 2.5 µm	50 ± 2.5 µm	62.5 ± 2.5 µm
Mode field diameter	1310 nm 9.0 ± 0.4 µm 1550 nm 10.1 ± 0.5 µm			
Cladding diameter	125 ± 0.7 µm	125 ± 1.0 µm	125 ± 1.0 µm	125 ± 1.0 µm
Primary coating diameter (nominal)	242 ± 7 µm	242 ± 5 µm	242 ± 5 µm	242 ± 7 µm
Attenuation (Maximum values)				
850 nm		≤ 2.7 dB/km	≤ 2.5 dB/km	≤ 3.2 dB/km
1300 nm		≤ 0.8 dB/km	≤ 0.8 dB/km	≤ 1.0 dB/km
1310 nm	≤ 0.39 dB/km			
1550 nm	≤ 0.25 dB/km			
Bandwidth(OFL)				
850 nm		>500 MHz·km	>1500 MHz·km	>200 MHz·km
1300 nm		>500 MHz·km	>500 MHz·km	>600 MHz·km
Chromatic Dispersion				
1285-1330 nm	≤ 3 ps/nm·km			
1550 nm	≤ 18 ps/nm·km			
1625 nm	≤ 22 ps/nm·km			
Polarization Mode Disp.				
Max. Individual Fibre	≤ 0.5 ps/√km			
PMD ₀ Link Design Value	≤ 0.2 ps/√km			
Group index of refraction				
850 nm		1.482	1.482	1.496
1300/1310 nm(MMF/SMF)	1.467	1.477	1.477	1.491
1550 nm	1.468			
1625 nm	1.468			

Minimum bending diameter of cable: 15 x outer diameter

Manufacturer Place

DNV GL ref. no. 136960

Application/Limitation

Temperature window

Operation: -40°C to +60°C
 Installation: -10°C to +60°C
 Storage: -40°C to +70°C

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

Type Approval documentation

Datasheets: D92aici.e23.doc dated 08.04.2014 & D92aici.e18, Sohome 2015-03.

Test reports: TT-94029 dated 09.02.94, TT-94030 dated 10.02.94, TT-94026 dated 09.02.94, TT-97048 dated 16.10.1997, TT-94028 dated 09.02.94, TT_D137AXAI_Tensili00.doc dated 28.06.2000
 Branttester dated 23.01.01

Job Id: **262.1-019769-1**
Certificate No: **TAE000000C**

Tests carried out

Tested according to IEC 60794-1/-2, IEC 60332-3-22, IEC 60332-3-24, IEC 60754-1/2 and IEC 61034-1/2

Marking of product

Bergen Cabling - part no. - AICI - fibre type

Periodical assessment

The scope of the periodical assessment to verify that the conditions stipulated for the Type approval is complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Production Sample Tests (PST) and Routines (RT) checked (if not available tests according to PST and RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment to be performed at least every second year.

END OF CERTIFICATE