

S09 1RU Black Sliding Patch Panel - 24 Position SC Duplex and LC Quad

The "S" range of patch panels are sliding draw style housings designed to house up to 48 fibers. They can be directly terminated by use of pre-terminated cable assemblies or spliced to pigtailed. The "S09" range is black in color and designed to house SC Duplex or LC Quad adaptors dependent upon your requirements, the panels include an internal mounting plate used to mount the adaptors for a secure fitment and improved fiber management. This 1RU sliding panel range offers multiple cable entry solutions with up to 4 standard cable entry points supporting loose tube, tight buffered and pre-terminated options additionally, a removal rear plate is incorporated to allow for installation of armored fiber cables. The S09 panel is offered unloaded and supported by a number of accessories available to order separately to allow the desired port count, please contact your sales representative for support. If loading this panel using LC Quad adaptors the adaptor count should not exceed 12 pieces.

Features

- Up to 48 fibers in 1RU
- Suitable for SC Duplex and LC Quad adaptors*
- 24 Adaptor positions
- Individually labeled ports
- 45° open working angle
- Accepts loose tube, distribution and pre-terminated cables
- RoHS and REACH SvHC
- Fits standard 19"

*If loading with LC Quad's the adaptor count should not exceed 12 pieces

Applications

- Data centers, premise installations, telecommunication networks
- Ethernet, Fiber Channel, ATM, LAN, MAN and WAN
- Data communication
- Indoor applications



Specifications

ELEMENT	CHARACTERISTIC
U Size	1RU (44.4mm)
Width	482mm
Depth	205mm
Net weight	2.5 kgs
Packaged weight	3 kgs
Packaged dimensions	530mm W X 55mm H x 260mm D
IP rating	IP20
Suitable for Adaptor type	SC Duplex
Number of ports	24
Cable Entry 20mm	2
Cable entry 25mm	2
Mounting Adjustment range	50mm
Material	Cold- rolled steel
Material thickness	1.2mm
Material coating	Powder coating
Colour	RAL 9004
Operating temperature	-40°C to +50°C
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754,
Materials Compliant to	RoHS, Reach/SVHC

Ordering Information

PART NUMBER	DESCRIPTION
S09XXX00-UB	Sliding Panel Black 24 Port (SCD) 48F UNLOADED

NOTE If loading with LC Quad's the adaptor count should not exceed 12 pieces