

Part. No: BC-13-240

Date 23/05-2015

Bergen Cabling DIN-Rail modular patchpanel

Front



Rear



6 port modular DIN-Rail Patchpanel

Compact Modular DIN-Rail patch panel in Stainless 316 steel . Can be filled with 6 LC duplex adaptors for a 12 fiber solution, or a mix of copper and fiber or other keystone adaptors.



Operating temperature: 0°C - 70°C

Storage/transport temperature: -40°C - 80°C

Relative humidity (non-condensing): 10% - 95%

Mechanical Construction

Dimensions : (H x D x W) 138 x 113 x 74 mm

Mounting Options: Rear DIN-Rail,

Weight: 0.8 kg

Protection class: IP20

Materials of Construction

Patch panel body and faceplate: Stainless steel 316

Including splice tray for 12 fibers and 1 gland. Prepared for 6 glands.

Cable Glands: Plastic (Maximum field cable diameter 12mm)

Ordering info

Part No.	Part Name
BC-13-240	BC DIN-Rail Patchpanel Empty
BC-11-004	BC Keystone connector Cat.6A STP
BC-12-284	BC Keystone adaptor for basic LC duplex and SC simplex adaptor
BC-12-287	BC Keystone adaptor ST SM/MM Red adaptor incl.
BC-12-280	BC Keystone adaptor HDMI F/F adaptor incl.
BC-12-283	BC Keystone adaptor F coax. Adaptor included
BC-12-281	BC Keystone adaptor RJ45 to RJ45 splice Cat.6
BC-12-283	BC Keystone blanking plug