

2U 48 PORTS SC SIMPLEX/LC DUPLEX SLIDING PATCH PANEL - SPP48S



Browse on Mobile

 Browse on Web

NEXCONEC® sliding patch panel accepts 48 adapters SC Simplex or LC Duplex within 2U space. The panel can be pre-loaded completely with the required adapters or pre-loaded with pigtails and splice accessories. The tray is locked by 2 plastic latches and lowers to a 45deg angle when fully extended. Installation and labelling are simple and easy.

FEATURES

- ✓ Recessed panel bracket mounting
- ✓ Up to 96FO in 2U space
- ✓ Fits standard 19" rack
- ✓ 8 Rear Cable entries

APPLICATIONS

- ✓ Enterprise network & Datacenter
- ✓ Indoor application
- ✓ Accepts Indoor and Outdoor Pre-terminated cables and conventional Splicing

SPECIFICATIONS

Mounting Type	Rack 19"
Height Unit	2U
Material	Cold rolled steel
Housing Color	Black
Application	Indoor IP20
Lockable	No
Dimensions (W x D x H in MM)	482 x 205 x 88.8
Net Weight	4.0 Kg

DESIGN - HARDWARE

Opening Type	Sliding Tray
Access Type	Front access
Front Cable Management	Optional
Cable Entry Direction	Rear
Rear Cable Management	8 Cable Entries (OD: 4x PG13.5 and 4x PG16 mm)
Slot Type	SC Simplex Footprint
Number of Slots	48
Fiber Capacity	48 with SC, 96 with LC

ORDER INFORMATION

Product	Part Number	Product Description
	SPP48S	2U 48 Ports SC Simplex Sliding Patch Panel Unloaded

CUSTOM PANEL KIT CONFIGURATOR

SPP48S	1	2	3	4
---------------	----------	----------	----------	----------

SPP48S	1	Adapter Type	2	Fiber Count	3	Adapter Color	4	Pigtails
	S1	SC	48	48FO	L	Blue	-	No Pigtails / Leave blank
	S2	SC/APC	72	72FO	N	Green	A1	SM OS2 G657A1
	L1	LC	96	96FO	E	Beige	O1	MM OM1
	L2	LC/APC		*72/96 in LC	Q	Aqua	O3	MM OM3
					V	Erika Violet	O4	MM OM4

- Panels KIT include Splice Kit (Splice Tray FSP01, Spool FSP02 and Cable Gland)
- Pigtails Tight Buffer Rainbow colored per default. Add E after pigtails for **Easy strip**, Example A1E
- Ask sales for other products and configuration not shown. sales@nexconec.com