

UX M 1000V P15/P108

Flame retardant conductors MUD resistant



GENERAL INFO

UX M 1000V P15/P108

Flame retardant conductors. Insulated conductor for earthing and bonding services. UX M 1000V meets the Oil & Mud resistance requirement in NEK TS 606:2022.

HF90 / SHF2 to IEC 60092-360 is a flame retardant halogen-free thermoset EVA rubber.

Marine;Offshore;Oil & Gas

CABLE CONSTRUCTION

Conductor material	Copper
Conductor surface	Tinned
Core insulation material	EVA rubber
Cable shape	Round
Max. conductor temperature [°C]	90

MARKING TEXT (EXAMPLE)

Cable marking example

"meter" "year/week" DRAKA 01 Part no. UX M 1000V P15/P108 1x 95 mm² IEC 332-3-22 Production no.

STANDARDS APPLIED



<p>NEK TS 606:2022 IEC 60092-353 IEC 60228 Class 2 or class 5 IEC 60092-350</p> <p>IEC 60332-1-2 and IEC 60332-3-22(Cat.A) IEC 60754-1 and IEC 60754-2</p> <p>IEC 61034-1, -2</p> <p>ISO 4892 part 3 Oil resistant IEC 60092-360 MUD resistant (IEC 60092-360 & NEK TS 606)</p>	<p>Cables for offshore installations Design standard Conductors General construction and test methods for power, control and instrumentation cables for shipboard and offshore applications Flame retardant properties Halogen free properties: IEC 60754-1 (pH ≥ 4,3, Conductivity ≤ 10μS), IEC 60754-2 (< 0,5% Halogen) Low smoke properties: IEC 61034-1, -2 (minimum 60% light transmittance) UV and Ozone resistance IRM 902 oil (168 hours @ 100°C) IRM 903 oil (168 hours @ 100°C), Calcium Bromide Brine (56 days @ 70°C), EDC 95-11 base oil (56 days @ 70°C)</p>
---	---

APPLICATION PROPERTIES

Test voltage [kV]	8.4
Min. outer temperature, fixed installation [°C]	-52
Max. outer temperature, fixed installation [°C]	75
Low temperature resistant (acc. EN 60811-504+505+506)	Yes
Outdoor installation	Yes
Min. outer temperature during installation [°C]	-20
Max. outer temperature during installation [°C]	50
Underground installation	Yes
Bending radius (rule)	6 x OD (cable overall diameter)
Certified for shipboard application	Yes

PRODUCT RANGE

SAP code	Basic construction	Colour outer sheath	Conductor category	EL no.	EAN-code (GTIN)	Commodity code
20109530	1x6mm ²	Green/yellow	Class 2 = stranded	1045541	7021528008005	85444941
20109531	1x10mm ²	Green/yellow	Class 2 = stranded	1045542	7021528008012	85444941
20109532	1x16mm ²	Green/yellow	Class 2 = stranded	1045543	7021528008029	85444941
20109533	1x25mm ²	Green/yellow	Class 2 = stranded	1045553	7021528008036	85444941
20109534	1x35mm ²	Green/yellow	Class 2 = stranded	1045563	7021528008043	85444941
20236384	1x35mm ² CI5	Green/yellow	Class 5 = flexible	20236384	7021528009040	85444941
20109535	1x50mm ²	Green/yellow	Class 2 = stranded	1045573	7021528008050	85444941
20109536	1x70mm ²	Green/yellow	Class 2 = stranded	1045583	7021528008067	85444941
20109537	1x95mm ²	Green/yellow	Class 2 = stranded	1045593	7021528008074	85444942
20172920	1x95mm ² CI5	Green/yellow	Class 5 = flexible	20172920	7021528009071	85444942
20121097	1x120mm ²	Green/yellow	Class 2 = stranded	1045603	7021528008081	85444942
20109538	1x150mm ²	Green/yellow	Class 2 = stranded	1045604	7021528008098	85444942
20139738	1x185mm ²	Green/yellow	Class 2 = stranded	20139738	7021528008104	85444942
20139739	1x240mm ²	Green/yellow	Class 2 = stranded	20139739	7021528008111	85444942
20204198	1x300mm ²	Green/yellow	Class 2 = stranded	20204198	7021528008128	85444942

DIMENSIONAL DATA

SAP code	Basic construction	Diameter conductor [mm]	Nominal thickness insulation [mm]	Nominal diameter over insulation [mm]	Cable weight [kg/km]	Copper weight [kg/km]
20109530	1x6mm ²	3.1	1	5.1	80	54
20109531	1x10mm ²	4	1	6	120	87
20109532	1x16mm ²	5.05	1	7.1	175	140
20109533	1x25mm ²	6.3	1.2	8.8	275	220
20109534	1x35mm ²	7.4	1.2	10	370	302
20236384	1x35mm ² CI5	8.45	1.2	11	380	306
20109535	1x50mm ²	8.75	1.4	12	500	411
20109536	1x70mm ²	10.6	1.4	13.5	715	608
20109537	1x95mm ²	12.35	1.6	16	955	820
20172920	1x95mm ² CI5	13.25	1.6	16.5	910	767
20121097	1x120mm ²	14	1.6	17.5	1,215	1,060
20109538	1x150mm ²	15.4	1.8	19.5	1,475	1,284
20139738	1x185mm ²	17.3	2	21.5	1,830	1,596
20139739	1x240mm ²	19.85	2.2	24.5	2,400	2,105
20204198	1x300mm ²	22.25	2.4	27.5	3,000	2,644

Conductor diameter tolerances for our Class 2 conductors are within the Lower and Upper Limits listed in IEC 60092-350 Annex D and Table D.1

ELECTRICAL VALUES POWER CABLES

SAP code	Basic construction	Conductor resistance at 20° C [Ohm/km]	Conductor resistance at operation temperature [Ohm/km]	Inductive Reactance (at 50Hz) [Ohm/km]	Inductive Reactance (at 60Hz) [Ohm/km]	Current carrying capacity [A]	Short circuit current (1sec) [kA]	Short circuit current (5sec) [kA]
20109530	1x6mm ²	3.11	3.97			52	0.84	0.37
20109531	1x10mm ²	1.84	2.35			72	1.4	0.62
20109532	1x16mm ²	1.16	1.48			96	2.24	1
20109533	1x25mm ²	0.734	0.936			127	3.5	1.56
20109534	1x35mm ²	0.529	0.675			157	4.9	2.19
20236384	1x35mm ² CI5	0.565	0.7204			157	4.9	2.19
20109535	1x50mm ²	0.391	0.499			196	7	3.13
20109536	1x70mm ²	0.27	0.344			242	9.8	4.38
20109537	1x95mm ²	0.195	0.249			293	13.3	5.94
20172920	1x95mm ² CI5	0.21	0.2677			293	13.3	5.94
20121097	1x120mm ²	0.154	0.196			339	16.8	7.51
20109538	1x150mm ²	0.126	0.161			389	21	9.39
20139738	1x185mm ²	0.1	0.128			440	25.9	11.58
20139739	1x240mm ²	0.0762	0.0972			522	33.6	15
20204198	1x300mm ²	0.0607	0.0774			601	42	18.7

Current Rating IEC 61892-4 Table 4 at 45°C ambient temperature. Maximum operating conductor temperature = 90°C

AMBIENT TEMPERATURE CORRECTION FACTORS

Ambient temperature °C / Omgivelsestemperatur °C	25	30	35	40	45	50	55	60	65	70	75	80	85
Rating factor / Korreksjonsfaktor	1,20	1,15	1,10	1,05	1,00	0,94	0,88	0,82	0,74	0,67	0,58	0,47	-

BENDING RADII & PULLING RECOMMENDATIONS

Minimum Bending Radius During Installation / Minimum bøyeradius under installasjon	Minimum Bending Radius Fixed Installed / Minimum bøyeradius ferdig installert	Maximum Tensile Load During Installation / Maksimum trekkraft ved installasjon	Minimum Installation Temperature / Minimum installasjons temperature
8 x D	6 x D	50 N x total cross section (mm ²) of conductors / 50 N x totalt ledertverrsnitt (mm ²)	- 20 °C

D = cable overall diameter

Maximum Tensile Load during installation shall not in any case exceed 20000N

© PRYSMIAN GROUP 2024, all rights reserved. All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorized by Prysmian Group.