OM4 Multimode Enhanced Pigtail

OM4 multimode enhanced pigtails are used to connect high speed networks like gigabit ethernet, fast ethernet and ethernet. The multimode pigtail buffer conforms to IEC, EIA TIA or Telcordia standards. The multimode pigtails are terminated with optimized connector which gives optimum optical performance.

Features

- SC, LC, ST, FC connectors
- Low smoke zero halogen (LSZH) buffer
- 900µm tight buffer or easy strip
- OM4 Pigtail is available in standard aqua color
- Multimode Fiber conforms to ITU-T G.651.1, TIA/EIA 492AAAA
- Different connector performance range for specific application
- Available in standard 12 colors as per IEC 60304
- Available in standard and blister packing
- REACH, RoHS & SvHC materials compliant

Applications

- Networks including Ethernet, Fast Ethernet and GBE
- Internal inter-connect
- Ideal for a wide range of telecom, datacom and process control applications where ruggedisation is required
- Suitable for repeated handling in patch panels and racks

Specifications

Connector Specification


OPTICAL PERFORMANCE	MULTIMODE	CONFORMANCE
IL Max/Master (Acceptance)	0.25 dB	IEC 61300-3-4
Ave/Master	0.15 dB	IEC 61300-3-4
Ave/Random	0.20 dB	IEC 61300-3-34

n/product/om4-multimode-enhanced-pigtail/. AFL reserves the right to make changes in this datasheet at any tim

Note: Return Loss ≥28dB based on sample data using method IEC 61300-3-6

Cable Specification





CHARACTERISTICS	UNITS	SIMPLEX
Crush	N/100 mm	500
Operating Temperature	°C	-20 to 60
Stripping Length - Easy Strip	m	1.5 minimum
Stripping Length - Tight buffer	mm	30 nominal
Nominal Buffer Diameter	μm	900 +/- 50
Max Tensile Load	N	6

Fiber Specification

CHARACTERISTICS	
Attenuation (dB / km)	2.8 @ 850 nm / 0.8 @ 1300 nm
Bandwidth OFL (MHz x km)	3500 @ 850 nm / 500 @ 1300 nm
Bandwidth EMBc (MHz x km)	4700 @ 850 nm

Ordering Information

Code		Cable Type		Fiber Count	(Code		Color		Grade	Con	necto r		Code		Unit	Len	gth
P4	AA	Easy Strip	1	Single Pigtail		L	6	WHITE	I	Е	AX	LC	-0000-	Single Pigtail	М	Meters	1	1
	AC	Tight Buffered	В	Pack of 12			С	AQUA			DX	SC	-0002-	12 in one Bag			2	2
							Н	12 Colours	Ι		ΗX	FC	-0004-	12 in Blister Pack	Τ			
									Τ		КΧ	ST						

Legacy Ordering Information

Connec	ctor End	Fiber	[.] Туре		Cat	ole Length		Cable Construction	
SC	SC	OM4	OM4	В	1	1 metre		Tight Buffer	
LC	LC				2	2 metre	-12/1B	Tight Buffer - Pack of 12 colours	
FC	FC				3	3 metre	BP12-TB	Tight Buffer - Blister pack of 12	
ST	ST				5	5 metre	EASY	Easy strip	
					10	10 metre	E-12/1B	Easy strip - Pack of 12 colours	
					хх	Specify	BP12	Easy strip - Blister pack of 12	

Example Part Number

SC OM4 B	5	-12/1B
----------	---	--------

This part number has created a 5 metre SC OM4 pack of 12 pigtails in different colours.

